Technical Specifications

Model SR1268AN	PL421AA
Processor & Speed	AMD A64 3200+ 2.2GHz (N)754
Chipset	SiS 760
Motherboard	Salmon-GL6E
RAM	512/3200 MB 400DDR SDRAM
Maximum	2 GB (2x1024MB DDR SDRAM)
Sockets	Two 184-pin DDR DIMMs
Size	128, 256, 512 AND 1024 MB DDR DIMMs
Free DIMM Sockets	One
Pairs Required	No
Type Supported	JEDEC unbuffered DDR SDRAM DIMM specification
Cache	128 KB L1, 512 KB L2 Integrated on Processor module
Hard Drive	80 GB (7200 rpm)
Optical Drive	8x DVD(+/-)R/RW DL Drive
Transfer rates	Write: Up to 40x (CD-R) Write: Up to 24x (CD-RW) Write: Up to 8x (DVD(+/-)R) Write: Up to 4x (DVD(+/-)RW) Write: Up to 2.4x (DVD+R DL) Read: Up to 40x (CD) Read: Up to 12x (DVD)
Diskette Drive	None
9 in 1 Card Reader	Compact Flash I/II, Memory Stick/PRO, MMC/SD, Smart Media, xD, Microdrive
Video Graphics	AGP 8X Graphics Card
Controller	nVidia FX5200XT
Video Memory	128 MB DDR, not upgradeable
Video Connectors	Composite & S-Video - PAL
Network Card	10/100 BaseT, Integrated
Wireless Lan	802.11b/g PCI Wireless
1394 Card	IEEE-1394, Integrated
Sound	AC'97, 6 Channel, Integrated on MB
Controller	Realtek ALC658
Chassis	Gobi, 250HV PSU
USB Interface Specification	USB 2.0
External I/O Rear Connectors	4= USB, 1=1394, Serial, Parallel, Line-In, Line-Out; Microphone
External I/O Front Connectors	1=1394, Line In; Microphone, Headphone, 9 in 1 Card Reader w/USB
Expansion Slots (Total)	3= PCI, 1=AGP
Expansion Slots (FREE)	3= PCI, 1=AGP
Drive Bays (Total)	Two 5.25" external, One 3.5" external, One 3.5" internal
Drive Bays (FREE)	One 5.25" external, One 3.5" external
Keyboard/Mouse	One-touch Enhanced Keyboard, PS/2 Optical scrolling mouse